V7 S19PD

Entertainment Line

With its slim silver-black design the 19“ display V7 S19PD will attract attention as a real eye catcher. The key application areas for this V7 LC-Display are games, videos and multimedia presentations but it´s also ideal for complex image processing programs or CAD/CAE applications. The special feature of this display is the excellent specification of 8 ms response time.

Specifications

Panel Size	19” (~ 483 mm)
Asepct Ratio	5:4 (~ 376 x 301 mm)
Panel Specification	CMO Panel, TN
Recommended Resolution	1280 x 1024
Pixel Pitch	0.294 mm
Colours max.	16.2 Mio
Brightness typ.	280 cd/m²
Contrast Ratio typ.	400:1
Viewing Angle H/V	150°/130°
Response Time typ.	8 (2/6) ms
Features	Speakers (2x 2W), internal power supply, Kensington® Security Port
Adjustment	Bightness, Contrast, Auto-Adjust, Clock, Phase, H/V-Position, Sharpness, Colour Control, OSD Position, Audio Control, Language, Recall etc.
Frequency at Resolution	640 x 480 @ 75 Hz 800 x 600 @ 75 Hz 1024 x 768 @ 75 Hz 1280 x 1024 @ 75 Hz
Horizontal Frequency	30 - 82 kHz
Vertical Frequency	56 - 76 Hz
Videobandwidth	135 Mhz
Input Signal	RGB Analog
Input Terminal	15pin D-Sub
Plug & Play	DDC2B
Power Management	VESA DPMS, ENERGY STAR
Power Consumption On/Off	58/1 Watt max.
Power Requirements	AC 100 - 240V, 50/60 Hz
Dimensions WxHxD **with stand** **without stand** **packaging**	 426 x 433 x 192 mm 426 x 376 x 50 mm 480 x 470 x 141 mm
Weight with/without stand **incl. packaging**	4.6 kg / 4 kg 6.1 kg
Tilt	20° ~ 0°
Operating Temperature	5-35/-20-55°C, Humidity: 20-80/20-85%
Wallmountable	VESA 100 x 100 mm
Certifications & Standards	CE, TÜV/GS, UL, FCC, TCO 03, ISO 13406-2
Supplied Accessories	12 language manual CD-Rom, power cable, VGA cable, audio cable
Pixel Criteria	bright <= 3, dark <= 3, total <= 7
Service	3 years on-site

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions are disclaimed. Measurement standards and testing conditions as per manufacturer definitions, available on request.
Issue: 02/2006